



HARDWARE REQUIRED:	PART #	QTY.
G - Joist Corner	DE99002F	52
H - Washer Plate	DE99006F	32
F - Backer Plate	DE93122F	8
K - Outside Corner	DE99004F	4
P - Chain Retainer	DE99013F	2
J - Howell 400 Float (shown)	DE99242F	5
Hardware Fastener Kit (8 pack Carriage Bolts, Lock Washers & Nuts)	DE85100F	18
Float Fastener Kit (8 pack Lag Bolts & Flat Washers)	DE85125F	4
U - Connector Pin	DE96111F	2
W - Male Corner Hinge	DE99009F	1 or 2
X - Female Corner Hinge	DE99010F	1 or 2
Y - Female T Connector	DE99012F	1 or 2
Z - Male T Connector	DE99011F	1 or 2

LUMBER REQUIRED:	LENGTH	QTY.
1 - End Stringer	2" x 6" x 240"	2
2 - Center Stringer	2" x 6" x 45"	10
3 - Cross Stringer	2" x 6" x 30"	4
4 - Cross Stringer	2" x 6" x 21"	5
5 - Deck Boards	5/4" x 6" x (At least 48")	40

IMPORTANT: CMP Group Ltd. assumes no responsibility or liability for the accuracy or representation of the graphic illustrations shown in this hardware guide. These graphic illustrations are not intended to be architectural drawings, and are not to be substituted for engineered drawings. Each is intended as a guideline ONLY. CMP Group Ltd. does not warrant the quantities and/ or bill of materials to be accurate in all uses and applications. Individual dock structures may vary by necessity, preference or design. It may be necessary to vary the amount of materials listed in this guide depending on dock size, material usage, necessity and/ or the severity of the conditions to which the dock structure is subjected to. All graphic illustrations are based on the use of conventional framework of 2" x 6" lumber and decking lumber. Freeboard may be adjusted by using 2" x 8" or 2" x 10" lumber. Substitutions in lumber and hardware placement may affect floatation.