



HARDWARE REQUIRED:

DESCRIPTION	PART #	QTY.
G - Joist Corner	DE95122F	18
H - Washer Plate	DE95123F	12
E - Corner Leg Holder	DE86100F	6
U - Side Leg Holder (optional)	DE86101F	4
M - Corner Leg Brace Holder	DE87107F	6
N - Side Leg Brace Holder	DE93105F	6
O - Adjustable Leg Brace Set	DE89101F	12
I - Leg Pipe 6'8"	DE93168F	6
Q - Bottom Pad	DE94102F	6
P - Base Plate (May be used in combination with or in place of Bottom Pad DE94102F)	DE86102F	
V - Pipe Cap	DE91111F	6
S - Chain Retainer (Use at outer most end of dock structure up to 16' & every 16' thereafter)	DE99013F	2
D - Backer Plate	DE87122F	18
Hardware Fastener Kit (8 pack Carriage Bolts, Lock Washers & Nuts)	DE85150F	14
F - Connector Hinge*	DE86103F	2
T - Corner Plate**	DE86104F	2

LUMBER REQUIRED:

DESCRIPTION	LENGTH	QTY.
1 - End Stringer	2" x 6" x 192"	2
2 - Cross Stringer	2" x 6" x 93.75"	6
3 - Side/ Center Stringer	2" x 6" x 93"	3
4 - Deck Boards	5/4" x 6" x (At least 96")	32

IMPORTANT: CMP Group Ltd. assumes no responsibility or liability for the accuracy or representation of the graphic illustrations shown in this hardware guide. These graphic illustrations are not intended to be architectural drawings, and are not to be substituted for engineered drawings. Each is intended as a guideline ONLY. CMP Group Ltd. does not warrant the quantities and/ or bill of materials to be accurate in all uses and applications. Individual dock structures may vary by necessity, preference or design. It may be necessary to vary the amount of materials listed in this guide depending on dock size, material usage, necessity and/ or the severity of the conditions to which the dock structure is subjected to. All graphic illustrations are based on the use of conventional framework of 2" x 6" lumber and decking lumber. Freeboard may be adjusted by using 2" x 8" or 2" x 10" lumber. Substitutions in lumber and hardware placement may affect floatation.

- * Connector Hinges used for between-dock and shore-to-dock or ramp connections and not required for individual dock sections.
- ** Corner plate hardware to be used at dock-to-shore connection of dock where leg support is not required.